

Seat No.: _____

Enrolment No. _____

GUJARAT TECHNOLOGICAL UNIVERSITY

BE - SEMESTER-V (NEW) - EXAMINATION – SUMMER 2017

Subject Code: 2150609

Date: 10/05/2017

Subject Name: Soil Mechanics

Time: 02:30 PM to 05:00 PM

Total Marks: 70

Instructions:

1. Attempt all questions.
2. Make suitable assumptions wherever necessary.
3. Figures to the right indicate full marks.

Q.1

Answer the following

14

- 1 The unit weight of soil at zero air voids depends on

A	Specific gravity	C	Water content
B	Unit weight of water	D	All of these
- 2 Compaction by vibratory roller is the best method of compaction in case of

A	Moist silty sand	C	Clay of medium compressibility
B	Well graded dry sand	D	Silt of high compressibility
- 3 The vertical stress at depth z directly below the point load P is (k is constant)

A	$k^*(P/z)$	C	$k^*(P/z^2)$
B	$k^*(P/z^3)$	D	$k^*(P/\sqrt{z})$
- 4 A 25 kN point load act on the surface of an infinite elastic medium. The vertical pressure intensity in kN/m^2 at a point 6.0 m below and 4.0 m away from the load will be

A	132	C	13.2
B	1.32	D	0.132
- 5 A direct shear test was conducted on a cohesionless soil ($c=0$) specimen under a normal stress of 200 kN/m^2 . the specimen failed at a shear stress of 100 kN/m^2 . the angle of internal friction of this soil is

A	26.6°	C	30.0°
B	29.5°	D	32.6°
- 6 For a sample of dry cohesionless soil with friction angle, Φ , the failure plane will be inclined to the major principal plane by an angle equal to

A	Φ	C	45°
B	$45^\circ - \Phi/2$	D	$45^\circ + \Phi/2$
- 7 Vane tester is normally used for determining in situ shear strength of

A	Soft clay	C	Stiff clay
B	sand	D	Gravel
- 8 The earth pressure for the design of bridge abutments is taken as

A	Active thrust	C	Thrust in at rest condition
B	Passive thrust	D	None of the above
- 9 Coulomb's theory of earth pressure is based on

A	The theory of elasticity	C	Empirical rules
B	The theory of plasticity	D	Wedge theory

- 10 A deep cut of 7 m has to be made in a clay with unit weight of 16 kN/m^3 and a cohesion of 25 kN/m^2 . What will be the factor of safety is one has to have a slope angle 30° ? Stability number is given to be 0.178(from Taylor's chart) for a depth factor of 3.

A	0.8	C	1.25
B	1.1	D	1.0

- 11 In friction circle method of slope analysis, if r defines the radius of the slip circle, the radius of friction circle is

A	$r \sin\Phi$	C	$r \cos\Phi$
B	r	D	$r \tan\Phi$

- 12 A footing $2\text{ m} \times 1\text{ m}$ exerts a uniform pressure of 150 kN/m^2 on the soil. Assuming a load dispersion of 2 vertical to 1 horizontal, the average vertical stress (kN/m^2) at 1.0 m below the footing is

A	50	C	80
B	75	D	100

- 13 The measure of soil compaction is its wet density. (True/False)

- 14 A foundation is considered as shallow if its depth is

A	less than 1 meter	C	equal to or less than its width
B	greater than its width	D	greater than 1 meter

- Q.2 (a) In a standard proctor test 1.8 kg of moist soil was filling the mould (volume=944 cc) after compaction. A soil sample weighting 23 g was taken from the mould and oven dried for 24 hours at a temperature of 110°C . Weight of the dry sample was found to be 20 g, specific gravity of soil solids is $G=2.7$. Find out theoretical maximum value of the dry unit weight of the soil at that water content. 03
- (b) Enlist and explain factors affecting compaction. 04
- (c) A concentrated load of 40 kN acts on the surface of a soil. Determine the vertical stress increment at points directly beneath the load upto a depth of 10m with an interval of 1 m and draw a plot. 07

OR

- (c) Plot the variation of vertical stress increment due to load on horizontal planes at depths of 1 m, 2 m and 3 m upto a horizontal distance of 3 m for 1 m interval on either side of centre. 07
- Q.3 (a) Write limitations of shear box tests. 03
- (b) Enlist and explain shear tests bases on drainage condition. 04
- (c) Explain triaxial test. 07

OR

- Q.3 (a) For a triaxial shear test conducted on a sand specimen at a confining pressure of 100 kN/m^2 under drained condition, resulted in deviator stress ($\sigma_1 - \sigma_3$) at failure of 100 kN/m^2 . Find the angle of shearing resistance. 03
- (b) Following results were obtained from an undrained shear box test on a soil 04
- | | | | |
|------------------|-----|-----|-----|
| Normal load (N) | 250 | 500 | 750 |
| Failure load (N) | 320 | 460 | 610 |
- Determine the strength parameters in terms of total stresses. The c/s area of shear box was 36 cm^2 .

- (c) Explain direct shear box test. 07
- Q.4 (a) An unsupported excavation is made to the maximum possible depth in a clay soil having $\gamma_r = 18 \text{ kN/m}^3$, $c = 100 \text{ kN/m}^2$, $\Phi = 30^\circ$. Find out active earth pressure, according to Rankine's theory, at the base level of the excavation. 03
- (b) Write about Initial, primary and secondary consolidation. 04
- (c) Derive equation for total force due to earth pressure at rest. 07

OR

- Q.4 (a) A retaining wall of height 8 m retains dry sand. In the initial state, the soil is loose and has a void ratio of 0.5, $\gamma_d = 17.8 \text{ kN/m}^3$ and $\Phi = 30^\circ$. Subsequently, the backfill is compacted to a state where void ratio is 0.4, $\gamma_d = 18.8 \text{ kN/m}^3$ and $\Phi = 35^\circ$. Find out the ratio of passive thrust to the final passive thrust, according to Rankine's earth pressure theory. 03
- (b) Determine the active pressure on the retaining wall shown in Fig. 1. 04
- (c) A clay layer whose total settlement under a given loading is expected to be 12 cm settles 3 cm at the end of 1 month after the application of load increment. How many months will be required to reach a settlement of 6 cm? How much settlement will occur in 10 months? Assume the layer to have double drainage. (For $T_v = 0.492$ $U = 76\%$) 07
- Q.5 (a) Differentiate between shallow and deep foundation. 03
- (b) In a laboratory, the consolidation test was performed on a specimen of clay 3 m thick. The sample was drained at top and bottom. The time required for 50% consolidation of the sample was observed to be 15 minutes. Determine the coefficient of consolidation of clay. 04
- (c) A cutting of depth of 10 m is to be made in soil which has $c = 30 \text{ kN/m}^2$, $\gamma = 19 \text{ kN/m}^3$ and $\Phi = 0$. There is a hard stratum below the original soil surface at a depth of 12 m. Find the safe slope of cutting if factor of safety is 1.5 for $D_r = 1.2$. ($S_u = 0.143$ for $i = 30^\circ$ and $S_u = 0.101$ for $i = 15^\circ$) 07

OR

- Q.5 (a) Enlist different types of foundations. 03
- (b) A long natural slope in an overconsolidated clay ($c' = 10 \text{ kN/m}^2$, $\Phi' = 25^\circ$ and $\gamma_{sat} = 20 \text{ kN/m}^3$) is inclined at 10° to the horizontal. The water table is at the surface and the seepage is parallel to slope. If a plane slip had developed at a depth of 5 m below the surface, determine the factor of safety. Take $\gamma_w = 10 \text{ kN/m}^3$. 04
- (c) Enlist and explain types of slope failures. 07




FIG-1