Seat No.: ____

Instructions:

Enrolment No.

GUJARAT TECHNOLOGICAL UNIVERSITY BE - SEMESTER-VI • EXAMINATION – SUMMER • 2014

Subject Code: 160503

Date: 23-05-2014

Subject Name: Process Equipment Design - I

Time: 10:30 am - 01:30 pm

Total Marks: 70

- 1. Attempt all questions.
- 2. Make suitable assumptions wherever necessary.
- 3. Figures to the right indicate full marks.
- Q-1 A horizontal 1-4 heat exchanger (condenser) is used to condense 45000 kg/hr of 14 mixed light hydrocarbon vapors. The condenser to operate at 10 bar. The vapor will enter the condenser saturated at 60 °C and the condensation will be completed at 45 °C. The average molecular weight of vapor is 52. The enthalpy of the vapor is 596.5 kJ/kg and the condensate 247 kJ/kg. Cooling water is available at 30 °C and the temperature rise is limited to 10°C. Plant standards requires tubes of 20 mm od, 16.8 mm id, 4.88 m long of admiralty brass. Use square pitch tube arrangement with $p_t=1.25d_0$. The vapors are to be totally condensed and no sub cooling is required. Take temperature correction factor $F_t=0.92$.

Based on overall heat transfer coefficient = 900 W/m²°C, Calculate

(1) Number of tubes (2) Shell Diameter (3) Tube side heat transfer coefficient and (4) Shell side heat transfer coefficient

Physical properties of condensate at 47°C are:

 $\mu_L = 0.16 \text{ mNs/m}, \rho_L = 551 \text{ kg/m}^3, k_L = 0.13 \text{W/m}^\circ\text{C}.$

Specific heat of water at $35^{\circ}C=4.18 \text{ kJ/kg C}$. Density of water = 993 kg/m³,

Thermal conductivity of water = 0.628 W/m °C.

- Q-2 A Hexane at 37.8 °C is pumped through the system at a rate of 10.1 m³/h. The tank of is at atmospheric pressure. Pressure at the end of discharge line is 345 kPa g. The discharge is 3.05 m above the pump center line while the suction lift is 1.22 m above the level of liquid in the tank. The friction loss in suction line is 3.45 kPa and that in the discharge line is 37.9 kPa. The mechanical efficiency of the pump is 0.6. The density of hexane is 659 kg/m³ and its vapor pressure at 37.8 C is 33.71 kPa. Calculate the power required by the centrifugal pump.
 - B Calculate the Manometer reading generated by orifice meter based on following 07 data:

Name of the fluid: Water Flow rate: 90000 kg/h Inside diameter of pipe=154 mm Operating temperature = 32 °C Density of water = 995 kg/m³ Viscosity of water = 0.765 cP Manometer fluid = Mercury, Density of mercury = 13516.47 kg/m³ Take $\beta = 0.5$. C₀=0.6055

OR

- **B** A three stage reciprocating compressor is used to compress 306 Sm³/h of **07** methane from 0.95 atm a to 59 atm a. The inlet temperature is 26.7 °C. Specific heat ratio of methane is 1.31. Calculate (1) Power required for compression, if mechanical efficiency is 70% and (2) discharge temperature of gas after 1st stage.
- Q-3 A sieve tray tower is used for stripping methanol from a feed of dilute aqueous 14 solution of methanol. The stripping heat is supplied by waste steam. Operating condition:

Vapor flowrate =3.0194 m³/s, Liquid flowrate= $5.011*10^{-3}$ m³/s Vapor composition= 20 mass% of methanol Liquid composition=15 mass% of methanol Liquid density=961 kg/m³, Vapor density in given condition=0.65329 kg/m³ Liquid surface tension= $40*10^{-3}$ N/m Temperature=368 K, Pressure=101325 Pa Tray spacing = 0.5 m, hole diameter = 5mm, A_h=0.07894 m² Weir height= 50mm, Weir length = 0.77(Di) For 85% flooding and 70% turn down ratio Calculate (1) tower diameter and (2) Check weather weeping takes place or not.

OR

Q-3 A 1. Discuss in brief the factors affecting selection of tray type.
 Q-3 A 2. State the functions of down comer in distillation column. Explain the different 03 types of down comers.

The feed and product composition for distillation column is given as below.							
Component	Feed (mol%)	Distillate (mol%)	Residue (mol%)				
n-butane	37	95	16.3				
Iso-pentane	32	5	41.6				
n-pentane	21		28.5				
n-hexane	10		13.6				

07

B

Determine the number of theoretical stages required for R=3, by FUG method.

Q-4	A B	Discuss in brief Random and Regular packing. Explain the important industrial applications of liquid-liquid extraction. OR	07 07
Q-4	A	 1)Explain advantages and disadvantages of vacuum distillation 2)Define: Weeping, Entrainment, Coning and Flooding in distillation column 	03 04
	В	Explain Tinker's flow model	07
Q-5		Venturi scrubber is used for absorbing NO _x gases from the exit gas stream of nitric acid plant by using 10% NaOH solution (by mass). The data for the scrubber is as follows. Volumetric flow rate of exist gas stream = 40,540 Nm ³ /h Discharge pressure of gas from venturi = Atmospheric Temperature of gas mixture, entering the venturi scrubber = 50 °C NO _x concentration in the exist gas stream = 2000 ppm (or mg/kg) Solvent = 10% NaOH Solution Solvent to gas ratio = 1.5 L/m^3 Throat velocity of gas phase = 100 m/s Average molar mass of flue gas = 28.43 kg/kmol Density of 10% NaOH Solution = 1075 kg/m^3 Equilibrium mass of NO _x per 100 mass ofH ₂ O = 0.025 Determine: (i) throat diameter of venturi scrubber (ii) % removal NO _x gases (iii) consumption of NaOH and (iv) pressure drop in venturi scrubber.	14
0.5		A feed stream having flow rate of 200 kg/h and containing 20 mass % acetic acid	

Q-5 A feed stream having flow rate of 200 kg/h and containing 20 mass % acetic acid in water is to be extracted at 25 0 C with 400 kg/h of recycled MIBK (Methyl IsoButyl Ketone) that contains 0.1 % acetic acid and 0.01 % water. The aqueous raffinate is extracted down to 1 % acetic acid. Calculate (i) N_{toR} considering MIBK and water as partially miscible liquids and (ii) N_{toR} considering MIBK and water as completely immiscible liquids and equilibrium curve as straight line (in

 $[\]alpha_{LK}$ =2.567, R_m=1.4509.

terms of mass ratio concentration).

Data for equilibrium curve:									
Х	0	0.0285	0.117	0.205	0.262	0.328	0.346		
Y	0	0.0187	0.089	0.173	0.246	0.308	0.336		

Data for operating curve:

X _S	0.2	0.14	0.08	0.01
Y _{S+1}	0.085	0.06	0.035	0.001

Data in terms of mass ratio:

X' (kg of Acetic	0	0.0299	0.1364	0.2708
acid/kg of water)				
Y' (kg of Acetic	0	0.0196	0.1039	0.2354
acid/kg of MIBK)				

Design Formulae:

(A) Heat Exchanger Design:

1. Tube bundle diameter, $D_b = d_0 \left[\frac{N_t}{k_1}\right]^{1/n_1}$

2. For square pitch arrangement with $P_t=1.25d_0$

No of tube side passes	1	2	4	6	8
k ₁	0.215	0.156	0.158	0.0402	0.0331
n ₁	2.207	2.291	2.263	2.617	2.643

3.Shell side condensation coefficient for horizontal position:

$$h_{co} = 0.95 k_L \left[\frac{\rho_L (\rho_L - \rho_v) g}{\mu_L \tau_h} \right]^{1/3} N_r^{-1/6}$$

Where $\tau_h = \frac{W_c}{LN_t}$ $N_r' = \frac{D_b}{p_t} N_r = \frac{2}{3} N_r'$

4. Tube side heat transfer coefficient:

For Nre>4000,

$$Nu = C \ Re^{0.8} Pr^{0.33} \left(\frac{\mu}{\mu_w}\right)^{0.14}$$

Where C=0.021 for gases, 0.023 for non viscous liquids, 0.027 for viscous liquids.

(B) Power required by centrifugal pump:

$$P = \frac{Hq_v \rho}{3.67*10^5 \eta}$$

(C) Orifice meter:

$$m = C_0 Y A_0 \sqrt{\frac{2g_c \Delta P \rho}{1 - \beta^4}}$$

(D) Compressor:

1.Power required for each stage:

$$P_{0} = \frac{2.78 \times 10^{-4}}{\eta} \frac{k}{k-1} q_{v1} P_{1} \left[\left(\frac{P_{2}}{P_{1}} \right)^{\frac{k-4}{k}} - 1 \right]$$

2. Temperature-Pressure relations:

$$T_2 = T_1 \left(\frac{P_2}{P_1}\right)^{\frac{k-1}{k}}$$

(E) Distillation Column:

1. Flooding velocity $v_F = C_f \left(\frac{\sigma}{0.02}\right)^{0.2} \left(\frac{\rho_L - \rho_v}{\rho_v}\right)^{0.5}$

2. Minimum vapor velocity to avoid weeping:

$$v_{h\,min} = \frac{K - 0.9(25.4 - d_h)}{\sqrt{\rho_v}}$$

3. Weir crest of liquid mm, $h_{ow} = 750 \left(\frac{L_m}{\rho_L l_w}\right)^{2/3}$

4.FUG Method:

Fenskey's Equation:

$$N_{m} = \frac{\log \left[\left(\frac{x_{LK}}{x_{HK}} \right)_{d} \left(\frac{x_{HK}}{x_{LK}} \right)_{b} \right]}{\log \propto_{LK}}$$
Gilliland's Correlation:

$$f(N) = \frac{N - N_{m}}{N + 1} = 1 - exp \left[\left(\frac{1 + 54.4\Psi}{11 + 117.2\Psi} \right) \left(\frac{\Psi - 1}{\Psi^{0.5}} \right) \right]$$
Where $\Psi = \frac{R - R_{m}}{R + 1}$

(F) Venturi scrubber:

1.Fractional solute removal =
$$\frac{y_1 - y_2}{y_1} = \eta \frac{(1 - mx_2 / y_2)}{\left(1 + \frac{mG_M}{L_M}\right)}$$

2. Mass transfer efficiency = $\eta = 1 - e^{-N_G}$

3.Number of overall gas-phase mass transfer units $N_G = (K_G a RT / p_t) / \theta_c$

4. Venturi pressure drop $\Delta P = 2.584 \times 10^{-3} v_G^2 \rho_G A_{th}^{0.133} (L'/G')^{0.78}$ (G) Extractor Design:

Number of overall mass transfer units based on raffinate phase:

- 1. For partially miscible system: $N_{toR} = \int_{X_{NP}}^{X_F} \frac{dX}{X X^*} + \frac{1}{2} \ln\left(\frac{1 X_{NP}}{1 X_F}\right) + \frac{1}{2} \ln\left(\frac{X_{NP}(r 1) + 1}{X_F(r 1) + 1}\right)$
- 2. For completely immiscible system:





