# **GUJARAT TECHNOLOGICAL UNIVERSITY** BE - SEMESTER-VI • EXAMINATION – WINTER • 2014

Subject Code: 163503 Subject Name: Fluid Flow and Heat Transfer Time: 02:30 pm - 05:00 pm Instructions: Date: 01-12-2014

## **Total Marks: 70**

- 1. Attempt all questions.
- 2. Make suitable assumptions wherever necessary.
- 3. Figures to the right indicate full marks.

Q.1

- (a) i) The shear stress at a point in a oil is 0.30 Pa and the velocity gradient at that point 04 is 0.25 per second. Find the viscosity of the oil, if the density of the oil is 970 kg/m<sup>3</sup>. Find also the kinematic viscosity of the oil.
  - ii) Explain the different kind of boundary conditions used in conduction heat transfer 03 studies.
  - (b) i) Write the principle of floatation with the condition of equilibrium of submerged 03 bodies.
    - ii) Pressurized water at 50 °C flows inside a 5 cm diameter, 1 m long tube with the 04 surface temperature maintained at 130 °C. If the heat transfer coefficient between water and tube is  $h = 2000 \text{ W/m}^2$  °C, determine the heat transfer rate from tube to the water.
- Q.2 (a) i) Discuss the boundary layer separation with the formation of boundary layer when a 07 fluid flows over a flat plate
  - ii) Water flows through a pipe of 5 mm diameter with a velocity of 1.6m/s. This pipe expands to a diameter of 12 mm. Calculate the volumetric flow rate of water flowing through expanded section.
  - (b) Find the density of a metallic body which floats at the interface of mercury of specific 07 gravity 13.6 and water such that 40% of its volume is submerged in mercury and remaining 60% is submerged in water.

### OR

- (b) A pipe of 250mm diameter carries an oil of specific gravity 0.8 at the rate of 140 07 liters/sec and under a pressure of 3 kPa. Find the total energy per unit weight at a point which is 3m above the datum line. Also find the total energy per unit mass and per unit volume.
- Q.3 (a) With a neat sketch explain the main parts, construction and working principle of orifice 07 meter? Derive the equation of discharge for an orifice meter.
  - (b) The maximum flow through a 300 mm diameter horizontal pipe line is 300 liters/sec. A 07 venturimeter is introduced at a point of the pipe where the pressure head is 5 m of water. Find the diameter of throat so that pressure at the throat is never negative. Take value of C<sub>d</sub> of venturimeter as 0.98.

### OR

**Q.3** (a) Brine is to be pumped through a 35 m long smooth copper tube having inside diameter 07 of 2.5-cm. The flow rate is  $94.7 \times 10^{-3}$  m<sup>3</sup>/min. Calculate the head loss due to friction. Data given: Specific gravity of brine = 1.18. Viscosity of brine = 2.5 cp. Use the below mentioned relation of 'f' and 'Re'

$$f = 0.0014 + \frac{0.125}{Re^{0.32}}$$

(b) Detail the various kinds of impellers used in process industries with kind of flow 07 patterns produced in them during agitation.

- Q.4 (a) Explain the significance of following dimensionless numbers i) Reynolds Number ii) 07
  Power number iii) Froude Number iv) Prandtl Number v) Nusselt Number vi) Biot
  Number vii) Grashoff Number
  - (b) An aluminum plate of k= 160W/m°C, density = 2790 kg/m<sup>3</sup> C<sub>p</sub> = 0.88 kJ/kg °C of 07 thickness L = 3 cm and at a uniform temperature of  $T_0 = 225$  °C is suddenly immersed at time t = 0 in a well stirred fluid maintained at a constant temperature T = 25 °C. The heat transfer coefficient between the plate and the fluid is 320 W/m<sup>2</sup> °C. Determine the time required for the plate to reach 50°C.

#### OR

- Q.4 (a) Explain the concept of "Fluidization" with various types involved and its application in 07 industry.
  - (b) A six-bladed turbine impeller is used to agitate an aqueous solution in a tank of diameter 0.5m. Impeller diameter is one-third tank diameter. The solution to be agitated has a viscosity of 1.01cp and density of 980 kg/m<sup>3</sup>. The turbine impeller turns at 300rpm. What will be the power required for agitation? (Take value of  $K_T = 6.3$ )
- Q.5 (a) i) Explain the significance of critical thickness of Insulation and Optimum thickness of 03 Insulation?
  - ii) Consider a hollow sphere of inner and outer radii  $r_i$  and  $r_o$ . Both the inner and outer **04** surfaces are isothermal and maintained at  $T_i$  and  $T_o$ . Develop an expression for steady state temperature distribution and heat transferred through the sphere.
  - (b) A shell and tube heat exchanger is used to cool 6 kg/sec of oil having a specific 07 heat of 2000 J/kg °C from 65 °C to 35 °C with 10 kg/sec of cooling water entering at 20 °C. The overall heat transfer coefficient is 600 W/(m<sup>2</sup> °C). Calculate the heat transfer area required in (i) parallel flow heat exchanger (ii) counter flow heat exchanger.

### OR

- Q.5 (a) Differentiate pool boiling and forced convection boiling? With a neat sketch explain the 07 various boiling regimes in forced convection boiling.
  - (b) A single effect evaporator is to be designed to concentrate 9000 kg/hr of a solution from 12% to 20% solids. Feed enters at 25 °C. Saturated steam at 110°C (latent heat = 540 kcal/kg) is available. The condensate leaves at the condensing temperature. Saturation temperature of vapor to the condenser is 400 °C ( $\lambda$ = 580 kcal/kg). Specific heat of all solutions may be taken as 1 kcal/kg °C. Boiling point rise is 5°C. The evaporator has an overall heat transfer coefficient of 1900 kcal/hr.m<sup>2</sup> °C.

Calculate: i) evaporator capacity ii) evaporator economy, iii) the area of heating surface required. Use 1 kcal = 4186 J.

\*\*\*\*\*