Seat No.:	nrolment No.
-----------	--------------

Subject code: 711006N

## **GUJARAT TECHNOLOGICAL UNIVERSITY**

M. E. - SEMESTER – I • EXAMINATION – WINTER 2012

Date: 16-01-2013

_		Name: Cryogenic Heat Exchangers(Elective) 2.30 pm – 05.00 pm Total Marks: 70	
Instr		-	
	1. 2. 3.	Attempt all questions.  Make suitable assumptions wherever necessary.  Figures to the right indicate full marks.  Student are allowed to use their own Properties tables	
Q.1	(a) (b)	coiled tubular heat exchanger (ii) cross flow plate fin heat exchangers (iii) Giauque Hampson coiled tubular heat exchanger.	07
	(6)	Explain the different boning phenomena regimes with near sketch.	07
Q.2	(a) (b)	homogeneous material with heat generation in steady state conditions.  A pipe of 100 mm OD passes through the centre of a concrete slab of cross	07 07
		section 60x60 cm. the outer surface of the pipe is maintained at 130°C while the outer surface of the concrete slab is at 30°C. Using the Graphical method of flux plot, estimate the heat loss per metre length of the pipe. Assume conductivity of concrete 1.37 W/m.K.	
	<b>(b)</b>	OR Discuss the conduction in fins considering the one dimensional case and derive the equation for the fin effectiveness.	07
Q.3	(a)	1	07
	<b>(b)</b>	pressure drop for cryogenic fluids.  In what important aspects, the cryogenic heat exchangers differ from those used in general services?  OR	07
Q.3	(a)		07
	<b>(b)</b>		07
Q.4	(a)	Determine the heat transfer coefficient for nitrogen gas flowing inside a straight circular tube having an inside diameter of 20 mm. The nitrogen gas is at a bulk temperature of 95 K, and the tube wall has a temperature of 105 K. the mass flow rate of the nitrogen is 40 g/s, and the gas pressure is 140 kPa. Also determine the pressure drop per unit length of tube for the conditions given.  Take properties as: $\mu$ = 6.98 $\mu$ Pa-s, $c_p$ = 1.067 kJ/kg-K, $k_t$ = 9.33 mW/m-K & Pr No. = 0.797. & Use the correlation = $j_H$ = 0.023 Re <sup>-0.20</sup> , $f$ = 0.184 Re <sup>-0.20</sup>	07
	<b>(b)</b>		07

- **Q.4** (a) A heat exchanger in counter flow Linde Hampson system operates with the **07** following parameters.
  - Warm fluid: air at 20.265 MPa, Mass flow rate = 1.25 kg/s.
  - $T_{h1} = 300 \text{ K}$ ;  $c_{p,hot} = 1.588 \text{ kJ/kg-K}$ ;
  - Cold fluid: air at 101.3 kPa; mass flow rate = 1.149 kg/s.
  - $T_{c1} = 81 \text{ K } c_{p,cold} = 1.017 \text{ kJ/kg-K};$
  - $U = 120 \text{ W/m}^2 \text{K}$ ;  $A = 70 \text{ m}^2$

Determine the heat transfer rate for this exchanger and the exit temperature of the two fluids.

- **Q.4** (b) Describe design procedure of cryogenic plate fin heat exchanger.
- Q.5 (a) Explain step by step design methodology for matrix type regenerator.
   (b) In plate-fin heat exchanger, the frontal area is 5.00 m<sup>2</sup> and the ratio of free
  - (b) In plate-fin heat exchanger, the frontal area is  $5.00 \text{ m}^2$  and the ratio of free flow area to frontal area is 0.40. The equivalent diameter of the flow passages is 3.60 mm. the gas flowing through the heat exchanger is methane ( $\mu = 0.015 \text{mPa-s}$ ), which flows through the heat exchanger at a mass flow rate of 25.0 kg/s. The density of the methane at the heat exchanger inlet is  $2.00 \text{ kg/m}^3$ , the density at the outlet is  $1.00 \text{kg/m}^3$ , and the density at the bulk condition is  $1.333 \text{kg/m}^3$ . The length of the core in the direction of the flow is 238.8 mm. The contraction co-efficient is  $K_c = 0.50$  and the expansion coefficient  $K_e = 0.30$ . The core friction factor correlation is given by  $f = 1.115 \text{Re}^{-0.25}$ . Determine the total pressure drop through the heat exchanger for the methane stream.

## OR

- Q.5 (a) A regenerator is constructed of 1.882 kg of metal spheres ( $C_s = 0.84 \text{ kJ/kg-K}$ , 09 ks = 155 W/m-K) the total cycle period is 4 seconds) the fluid flowing through the regenerator is helium gas ( $c_p = 5.2 \text{ kJ/kg-K}$ ) for both streams. The mass flow rate of hot stream and cold stream is 40g/s and 36 g/s respectively. The convective heat transfer co-efficients are  $h_c = h_h = 8320 \text{W} / \text{m}^2 \text{K}$ , and the heat transfer area Ah=Ac = 0.950 m<sup>2</sup>. Determine the regenerator effectiveness.
  - (b) Write a note on regenerators. Also state its advantages and disadvantages as 05 compared to recuperators.

\*\*\*\*\*

**07**