Enrolment No.

GUJARAT TECHNOLOGICAL UNIVERSITY M. E. - SEMESTER – I • EXAMINATION – WINTER • 2013

Subject code: 712101N

Date: 23-12-2013

Subject Name: Applied Thermodynamics & Heat Transfer Time: 10.30 am – 01.00 pm Total Marks: 70

Instructions:

- 1. Attempt all questions.
- 2. Make suitable assumptions wherever necessary.
- 3. Figures to the right indicate full marks.
- Q.1 (a) Derive the expression for the useful work done for the system undergoing a 07 steady flow process in the following form

$$W = \sum m_i \left(h_i + \frac{V_i^2}{2} + gz_i - T_0 s_i \right) - \sum m_e \left(h_e + \frac{V_e^2}{2} + gz_e - T_0 s_e \right) - T_0 s_{gen}$$

- (b) A piston cylinder device contains 0.05 kg of steam at 1 MPa and 300°C. The steam now expands to a final state of 200 kPa and 150°C, during work. Heat losses from a system to the surroundings are estimated to be 2 kJ during this process. Assuming the surroundings to be at $T_0 = 25$ °C and $P_0 = 100$ kPa. Determine the availability of steam at the initials and the final states.
- **Q.2** (a) Derive a relation for the Jule-Thomson coefficient and the inversion 07 temperature for a gas whose equation of state is $(P + a/v^2) = RT$
 - (b) Estimate the Joule-Thomson coefficient of steam at (a) 3 MPa and 300°C and
 (b) 6 MPa and 500°C.

OR

- (b) Using the Maxwell relations and the ideal gas equation of state, show that $\left(\frac{\partial s}{\partial y}\right)_{r} = \frac{R}{y}$
- Q.3 (a) Explain the concept of Phase equilibrium for single component system. 07
 - (b) A mixture of 3 kmol of CO, 2.5 kmol of O_2 and 8 kmol of N_2 is heated to form O7 CO₂ and CO. Assumed that the remaining O_2 and N_2 will not dissociate, determine the equilibrium composition of the mixture. Take the value of equilibrium constant Kp = 16.46.

OR

- Q.3 (a) A long solid cylinder of radius r_o having uniform heat generation at the rate of g_0 . Its outer surface is maintained at temperature T_s . If the center temperature is T_c , show that the temperature distribution in radial direction is given by $\frac{T T_s}{T_c T_s} = 1 \frac{r^2}{r_o^2}$
 - (b) A plane wall of thickness 0.1 m and thermal conductivity 25 W/m K having uniform volumetric heat generation of 0.3 MW/m³ is insulated on one side while the other side is exposed to a fluid at 92°C. The convection heat transfer coefficient between the wall and the fluid is 500 W/m²K. Determine the maximum temperature in the wall.
- Q.4 (a) If a thin and long fin, insulated at its tip is used, show that the heat transfer 07 from the fin is given by

$$Q_{fin} = \sqrt{hPkA_c} \left(T_0 - T_\infty\right) \tanh mL$$

1

(b) Aluminum sphere weighing 6 kg and initially at temperature of 350°C is suddenly immersed in a fluid at 30°C with convective coefficient of 60 W/m²K. Estimate the time required to cool the sphere to 100°C. take thermodynamic properties of aluminum as

 $C = 900 \text{ J/kgK}, \rho = 2700 \text{ kg/m}^3, \text{ k} = 205 \text{ W/mK}$

OR

- Q.4 (a) Explain the Prandtl mixing length concept to describe turbulent flow over a flat 07 surface.
 - (b) Air at 10°C and at a pressure of 100 kPa is flowing over a plate at a velocity of 3 m/s. If the plate is 30 cm wide and at a temperature of 60°C. Calculate the following quantities at x = 0.3.
 - 1. Boundary layer thickness
 - 2. Thermal boundary layer thickness
 - 3. Heat transfer from the plate
- Q.5 (a) Explain the following term in relation with natural convection heat transfer 07 including its physical significance
 - 1. Buoyancy force
 - 2. Rayleigh number
 - 3. Grashof number

(b) Explain the following terms in relation with radiation heat transfer. 07

- 1. Solid angle
- 2. Radiosity
- 3. Radiation intensity

OR

Q.5	(a)	Explain Wien's displacement law of radiation.	07
	(b)		07
		1000 W/m^2 . If the surface area is 0.1 m ² . Calculate	
		1. Radiosity of the surface	

- 2. Net radiative heat transfer rate from the surface
- 3. Calculate above quantity if surface is black.
